

POWERTRACKER® MPS-25ES



www.efinet.com

METAL SURGE PROTECTION DEVICE

EFI's PowerTracker plug-in surge protection devices put protection where it can do the most good to isolate and protect your most sensitive equipment. Each solution features high quality surge suppression and noise filtration, and can also be conveniently installed at any standard power outlet to eliminate disruptive and damaging electrical disturbances. The PowerTracker line provides you with a choice of solutions to best meet your specific application needs. Compliant with UL 1449 2.5 Edition.

APPLICATIONS

The PowerTracker plug-in surge protection products provide guaranteed protection for all types of applications, including; industrial, medical, commercial and residential equipment.

SUPERIOR PERFORMANCE

The MP-25ES utilizes a suppression circuit that provides up to 39,000 amps of surge protection, 270 joules, and EMI/RFI noise filtration.

The MP-25ES surge protection product meet the latest UL listing for surge protection devices, UL 1449 2.5 Edition.

EASY INSTALLATION

The PowerTracker installs quickly and easily to standard electrical outlets, and it's compact design allows it to be concealed behind or under work stations or furniture. Users can choose to simply rest the PowerTracker on the floor or to mount it on the bottom or side of furniture through the mounting slots on the bottom of the product.



FEATURES	ADVANTAGES	BENEFITS
COMPACT DESIGN	Conveniently installs under or behind workstations or furniture	Hides unsightly cord snarls
RED STATUS LED INDICATOR	Provides continuous status indicator	Prevents unknown loss of protection

POWERTRACKER® MPS-25ES Product Specifications



PERFORMANCE

Max Surge Current	39,000 Amps
EMI/RFI Noise Rejection	Up to -52 dB
Continuous Current	15 Amps
MCOV	150VAC
Service Voltage	130VAC
Clamping Voltage	400V peak
Energy Rating	270 Joules per Mode
Response Time	Instantaneous
Operating Frequency	50/60/400 Hz
Protection Modes	L-N, L-G, N-G
AC Power Cord	6 ft.

MECHANICAL DESCRIPTION

Dimensions	1.25" x 12.25" x 2.25"
Housing	Metal
Housing Color	White
Receptacles	6
Circuit Type	High Energy, Multi-Stage Hybrid

DIAGNOSTICS

Red Status LED	Indicates ground and power protection
----------------	--

SAFETY APPROVALS

UL 1449 2.5 Edition

WARRANTY

Product Lifetime

MPS-25ES

